

UNIVERSAL 3/2 AND 5/2 NAMUR SOLENOID VALVE

ONE SOLENOID FITS ALL BI-TORQ PNEUMATIC ACTUATOR MODELS*--NO EXTRA PIPING REQUIRED



IDEAL FOR USE ON BI-TORQ SPRING RETURN AND DOUBLE ACTING PNEUMATIC ACTUATORS


*NAMUR adaptor block required on PN-32-DA

FEATURES AND BENEFITS

- Pilot operated spool valve design
- 3/2 or 5/2 field selectable for double acting and spring return actuators
- High flow 1.8 cV
- Integral push-button manual override
- Easy change-out coils
- DIN and strain relief connectors available
- Rapid response time (up to 5 cycles/sec)
- 100% continuous duty cycle

Ideal for a variety of pneumatic actuator applications, including petrochemical, pulp and paper, filling equipment, food processing and water treatment.

AV-SOL-4 (NEMA 4 COIL)



All units are mounted and cycle-tested with air and electrical signals.

NEMA 7/9, flying leads, and intrinsically-safe coils are available on the standard AV body.



TECHNICAL SPECIFICATIONS

STANDARD BODY MATERIAL

Anodized aluminum (SS optional)

STANDARD SEAL MATERIAL

BUNA-N (+14°F to +176°F)

AVAILABLE COIL VOLTAGES

12VDC, 24VDC, 120VAC, 220VAC, 24VAC

STANDARD PROTECTION CLASS

NEMA 4 (NEMA 7 optional)

ELECTRICAL CONNECTION

Strain relief or DIN connector

AMBIENT TEMPERATURE

+14°F to +122°F

MEDIA

Compressed air (filtered and lubricated)

OPERATING PRESSURE

35PSI - 150PSI

COIL INSULATION: Class F

35PSI - 150PSI