



THERMAL-ELECTRIC SHUT-OFF (TES) VALVES

BI-TORQ Valve Automation offers a Thermal-Electric Shut-off model in its thermal shut-off line of fire safety valves. A Thermal-Electric Shut-off valve allows an operator to trigger a single assembly or bank of them with a low voltage signal. When voltage is applied to the thermal-electric link directly from a PLC or other command device, the link will yield, the spring pack unwinds and the valve will close. The links also yield when the ambient temperature reaches the rated temperature of the link.


LARGER SIZE RANGE AND NEW DESIGN

OVERVIEW

A thermal-electric safety shut-off valve adds another layer of control when it comes to a facility's ability to isolate tanks and key points in a piping system. The ability to systematically shut down a large group of valves from a central control point, **due to a fire or other emergency**, without having to worry about adding pneumatic lines, additional compressors, or costly spring return electric actuators makes the thermal-electric solution a clean, **maintenance free and cost-effective** decision over the long term.

HOW THEY WORK

When a 0.2 ampere minimum trip current is applied to the link (50 millisecond minimum duration) a chemical reaction starts, which heats the link core and causes separation of the link in 6 to 10 seconds. Links can be used outdoors with optional enclosure.



CAPABILITIES

With the ability to now offer models up to 3,960 in./lbs (typically 6" ball valves and 12" butterfly valves), the product can be introduced into applications with large tanks and piping systems, expanding the overall coverage of our fire safety valves.

The Thermal-Electric Shut-off models are offered the same two ways as our Thermal Shut-off Valves (FLP/FL series) - a complete package including a BI-TORQ fire safe valve or factory mounted on a customer-specified or AML valve.

Contact your local BI-TORQ representative or email us at marketing@bitorq.com to learn more our fire safety suite of products and how they can protect a facility.

FOR CRITICAL APPLICATIONS INVOLVING

FLAMMABLE LIQUID 3 **FLAMMABLE GAS 2** **TOXIC 6**

IDEAL FOR TANK FARMS, HYDRAULIC SYSTEMS, FUELING DEPOTS AND LOADING/UNLOADING RACKS

BI-TORQ PACKAGES:

- 1/4" through 6" fire safe ball valves
- 2" through 12" fire safe butterfly valves
- 6,000 PSI HP NPT fire safe ball valves

