

## Valve Actuation Data Sheet

## FIRE SAFE FUSIBLE LINK VALVES

| CONTACT INFORMATION  |  |
|--|--|
| COMPANY  |  |
| Contact  | Fax  |
| <b>D</b> ате   | E-mail   |
| VALVE AND MEDIA INFORMATION  |  |
| VALVE TYPE/SIZE  | Temperature  |
| Media  Torque Required (if customer owned valve)   | Line Pressure  |
| BODY & TRIM MATERIAL: BALL VALVE  BODY MATERIAL END CONNECTIONS SEAT MATERIAL  CARBON STEEL X SS NPT TEE  STAINLESS STEEL SOCKET WELD RTFE  OTHER (SPECIFY) BUTT WELD DELRIN  150# FLANGED PEEK  300# FLANGED NOVA  METAL  | BODY & TRIM MATERIAL: BUTTERFLY VALVE  BODY MATERIAL DISC MATERIAL SEAT MATERIAL  CAST IRON DUCTILE IRON EPDM  STAINLESS STEEL STAINLESS STEEL VITON  ALUMINUM BRONZE BUNA-N  TFE  METAL  END CONNECTIONS  WAFER LUG |
| ASSEMBLY INFORMATION   | Additional Application Notes   |
| FAIL OPEN FAIL CLOSED  LINK YIELD TEMPERATURE  135° 212° 360°  165° 280° 440°  AMBIENT TEMPERATURE  INDOOR INSTALLATION OUTDOOR INSTALLATION  POSITION INDICATOR OPEN CLOSED  PIPELINE MOUNTING VERTICAL HORIZONTAL  AVAILABLE CLEARANCE  VERTICAL HORIZONTAL  APPLICATION AND ENVIRONMENT |  |